



AC Three-phase Motors - IE4/IE3/IE2/IE1

SUPER PREMIUM EFFICIENCY MOTORS - IE4/CURUS

- Wide range from 0.75 to 200kW
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs



TECHNICAL DATA

Motor Type

AMQE 250M PG2 - 55 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 250M PG
Poles	2
kW	55
HP	75
rpm	2975
Mn Nm	176.6
η 50%	93.4
η 75%	95.3
η 100%	95.3
cos Phi	0.90
I _N 400V	92.6
I _N 460V	-
I _N 575V	-
I _A /I _N	7.7

M_A/M_N	2.0
M_S/M_N	1.8
M_K/M_N	2.3
$J \cdot 10^{-3} \text{ kgm}^2$	312
kg	520

Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	6314 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	1.000 hours
Regreasing device vertical	1.000 hours
Grease Quantity	35 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	81

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.