



AC Three-phase Motors - IE4/IE3/IE2/IE1

SUPER PREMIUM EFFICIENCY MOTORS - IE4/CURUS

- Wide range from 0.75 to 200kW
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs



TECHNICAL DATA

Motor Type

AMQE 132S AA44 - 4 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 132S AA4
Poles	4
kW	4
HP	5.5
rpm	1477
Mn Nm	25.9
η 50%	89.0
η 75%	90.7
η 100%	91.1
cos Phi	0.79
I _N 400V	8.1
I _N 460V	-
I _N 575V	-
I _A /I _N	10.2

M_A/M_N	4.6
M_S/M_N	3.9
M_K/M_N	4.4
$J \cdot 10^{-3} \text{ kgm}^2$	33.0
kg	49.0

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	59

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V - ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.