



AC Three-phase Motors - IE4/IE3/IE2/IE1

SUPER PREMIUM EFFICIENCY MOTORS - IE4/CURUS

- Wide range from 0.75 to 200kW
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs



TECHNICAL DATA

Motor Type

AMQE 160L CA44 - 15 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 160L CA4
Poles	4
kW	15
HP	20
rpm	1480
Mn Nm	97.4
η 50%	91.8
η 75%	93.3
η 100%	93.9
cos Phi	0.80
I _N 400V	29.0
I _N 460V	-
I _N 575V	-
I _A /I _N	8.1

M_A/M_N	1.9
M_S/M_N	1.3
M_K/M_N	3.0
$J \cdot 10^{-3} \text{ kgm}^2$	135.0
kg	125.0

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.