



AC Three-phase Motors - IE4/IE3/IE2/IE1

SUPER PREMIUM EFFICIENCY MOTORS - IE4/CURUS

- Wide range from 0.75 to 200kW
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs



TECHNICAL DATA

Motor Type

AMQE 315L RG4 - 160 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 315L RG
Poles	4
kW	160
HP	200
rpm	1490
Mn Nm	1026.0
η 50%	94.7
η 75%	96.6
η 100%	96.6
cos Phi	0.89
I _N 400V	269.0
I _N 460V	-
I _N 575V	-
I _A /I _N	7.1

M_A/M_N	2.0
M_S/M_N	1.9
M_K/M_N	2.2
$J \cdot 10^{-3} \text{ kgm}^2$	4130
kg	1093

Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	NU319 - 6319 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	3.800 hours
Regreasing device vertical	3.800 hours
Grease Quantity	50 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	71

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.