



## AC Three-phase Motors - IE4/IE3/IE2/IE1

### TWO SPEED MOTORS

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



## TECHNICAL DATA

Motor Type

AM 90L BA4/6 - 1/0.65 kW - 4/6 poles - 400V - 50Hz

## PERFORMANCE DATA

Type	AM 90L BA
Poles	4/6
kW	1/0.65
HP	1.34/0.7
rpm	1380/920
Mn Nm	6.9/6.7
$\eta$ 100%	68.8/67.1
cos Phi	0.81/0.62
$I_N$ 400V	2.6/2.3
$I_N$ 380-420V	2.8/2.5
$I_A/I_N$	2.9/3.4
$M_A/M_N$	1.1/1.6
J $10^{-3}$ kgm <sup>2</sup>	4.78
kg	16.4

## Mechanical Data

<b>Design</b>	Aluminium
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6205/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	49

## Electrical Data

<b>Voltage</b>	400V - 50Hz
<b>Connection</b>	SEPARATE WINDINGS