



## AC Three-phase Motors - IE4/IE3/IE2/IE1

### TWO SPEED MOTORS

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



## TECHNICAL DATA

**Motor Type** AMV 100L BA4/2 - 0.6/3 kW - 4/2 poles - 400V - 50Hz

## PERFORMANCE DATA

<b>Type</b>	AMV 100L BA
<b>Poles</b>	4/2
<b>kW</b>	0.6/3
<b>HP</b>	0.8/4
<b>rpm</b>	1440/2850
<b>Mn Nm</b>	4/10.1
<b><math>\eta</math> 100%</b>	78/77
<b>cos Phi</b>	0.79/0.87
<b><math>I_N</math> 400V</b>	1.3/6.2
<b><math>I_N</math> 380-420V</b>	1.4/6.5
<b><math>I_A/I_N</math></b>	4.5/4.5
<b><math>M_A/M_N</math></b>	2.2/2.1
<b>J 10<sup>-3</sup> kgm<sup>2</sup></b>	5.58
<b>kg</b>	23.2

## Mechanical Data

<b>Design</b>	Aluminium
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6206/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	66

## Electrical Data

<b>Voltage</b>	400V - 50Hz
<b>Connection</b>	DAHLANDER - Y/YY