



AC Three-phase Motors - IE4/IE3/IE2/IE1

TWO SPEED MOTORS

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AMV 80Z AA4/6 - 0.55/0.18 kW - 4/6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMV 80Z AA
Poles	4/6
kW	0.55/0.18
HP	0.75/0.25
rpm	1380/920
Mn Nm	3.8/1.9
η 100%	60/42
cos Phi	0.83/0.82
I_N 400V	1.60/0.75
I_N 380-420V	1.7/0.8
I_A/I_N	3.5/2.4
M_A/M_N	1.6/1
J 10^{-3} kgm ²	1.97
kg	8.3

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6204/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	48

Electrical Data

Voltage	400V - 50Hz
Connection	SEPARATE WINDINGS