



## AC Three-phase Motors - IE4/IE3/IE2/IE1

### TWO SPEED MOTORS

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



## TECHNICAL DATA

Motor Type

AMV 100L AA4/6 - 1.85/0.6 kW - 4/6 poles - 400V - 50Hz

## PERFORMANCE DATA

Type	AMV 100L AA
Poles	4/6
kW	1.85/0.6
HP	2.5/0.75
rpm	1400/920
Mn Nm	12.6/6.2
$\eta$ 100%	74/64
cos Phi	0.8/0.73
$I_N$ 400V	4.6/1.9
$I_N$ 380-420V	4.8/2.1
$I_A/I_N$	4.8/3.1
$M_A/M_N$	1.8/1.5
J $10^{-3}$ kgm <sup>2</sup>	6.73
kg	23.4

## Mechanical Data

<b>Design</b>	Aluminium
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6206/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	50

## Electrical Data

<b>Voltage</b>	400V - 50Hz
<b>Connection</b>	SEPARATE WINDINGS