



Brushless Servo Motors

SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



TECHNICAL DATA

Motor Type

B28.D7Q 0.75 Nm - 6000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B28.D7Q
Stall torque (Deltat=105°C) Mo Nm	0.75
Rated speed n rpm	6000
Rated power P _n kW	440
Rated torque (Deltat=105°C) Mn Nm	0.70
Peak torque M _{pk} Nm	3
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	0.19
Peack torque acceleration a _{pk} rad/sec ²	157895
Thermal time constant T _{th} min	36
Voltage constant k _e V _s	0.42
Torque constant k _t Nm/A	0.73
Resistance phase to phase (20°C) R _w ?	24.2
Inductance phase to phase L _w mH	38.8

B.E.M.F. @ rated speed E_n Vrms	264
Stall current I_o Arms	1.03
Rated current I_n Arms	0.96
Peak current I_{pk} Arms	5
Power connector size	7/1
Weight kg	1.5

Mechanical Data

Design	Aluminium
Degree of protection	IP 65 except A side flange
Bearings DE	6000 2ZC3WT
Bearings NDE	6900 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	8
Voltage	400V
Thermal protection threshold θ_{max} °C	140