



### Brushless Servo Motors

### SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



## TECHNICAL DATA

Motor Type

B10.42J 55.4 Nm - 2000 rpm - 10 poles - 400V

## PERFORMANCE DATA

Type	B10.42J
Stall torque (Deltat=105°C) Mo Nm	55.4
Rated speed n rpm	2000
Rated power P <sub>n</sub> kW	10.5
Rated torque (Deltat=105°C) Mn Nm	50
Peak torque M <sub>pk</sub> Nm	180
Max speed n <sub>max</sub> rpm	4000
Moment of inertia J 10?? Kgm <sup>2</sup>	74
Peack torque acceleration a <sub>pk</sub> rad/sec <sup>2</sup>	24324
Thermal time constant T <sub>th</sub> min	46
Voltage constant k <sub>e</sub> V <sub>s</sub>	1.41
Torque constant k <sub>t</sub> Nm/A	2.44
Resistance phase to phase (20°C) R <sub>w</sub> ?	0.5
Inductance phase to phase L <sub>w</sub> mH	8.8

<b>B.E.M.F. @ rated speed <math>E_n</math> Vrms</b>	296
<b>Stall current <math>I_o</math> Arms</b>	22.7
<b>Rated current <math>I_n</math> Arms</b>	20.4
<b>Peak current <math>I_{pk}</math> Arms</b>	105
<b>Power connector size</b>	7/1
<b>Weight kg</b>	30

## Mechanical Data

<b>Design</b>	Aluminium
<b>Degree of protection</b>	IP 65
<b>Bearings DE</b>	6208 2ZC3WT
<b>Bearings NDE</b>	6206 2ZC3WT
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device</b>	permanent lubrication
<b>Cooling</b>	radiation and natural convection
<b>Vibration Level</b>	A (normal)

## Electrical Data

<b>Poles</b>	10
<b>Voltage</b>	400V
<b>Thermal protection threshold <math>\theta_{max}</math> °C</b>	140