



Brushless Servo Motors

SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



TECHNICAL DATA

Motor Type

B30.E4J 1.4 Nm - 6000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B30.E4J
Stall torque (Deltat=105°C) Mo Nm	1.4
Rated speed n rpm	6000
Rated power P _n kW	700
Rated torque (Deltat=105°C) Mn Nm	1.1
Peak torque M _{pk} Nm	4.8
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	0.41
Peack torque acceleration a _{pk} rad/sec ²	117073
Thermal time constant T _{th} min	20
Voltage constant k _e V _s	0.47
Torque constant k _t Nm/A	0.81
Resistance phase to phase (20°C) R _w ?	9.9
Inductance phase to phase L _w mH	12.9

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	1.72
Rated current I_n Arms	1.35
Peak current I_{pk} Arms	6.9
Power connector size	8/-
Weight kg	1.7

Mechanical Data

Design	Aluminium
Degree of protection	IP 65 except A side flange
Bearings DE	6002 2ZC3WT
Bearings NDE	6900 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	10
Voltage	400V
Thermal protection threshold θ_{max} °C	140