



Brushless Servo Motors

SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



TECHNICAL DATA

Motor Type

B13.98I 98 Nm - 3000 rpm - 6 poles - 400V

PERFORMANCE DATA

Type	B13.98I
Stall torque (Deltat=105°C) Mo Nm	98
Rated speed n rpm	3000
Rated power P _n kW	19
Rated torque (Deltat=105°C) Mn Nm	60.5
Peak torque M _{pk} Nm	280
Max speed n _{max} rpm	3600
Moment of inertia J 10?? Kgm ²	150
Peack torque acceleration a _{pk} rad/sec ²	18667
Thermal time constant T _{th} min	80
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	0.08
Inductance phase to phase L _w mH	2.2

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	60.1
Rated current I_n Arms	37.1
Peak current I_{pk} Arms	217
Power connector size	7/1.5
Weight kg	83

Mechanical Data

Design	Aluminium
Degree of protection	IP 65 except A side flange
Bearings DE	6309 2ZC3WT
Bearings NDE	6208 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	6
Voltage	400V
Thermal protection threshold θ_{max} °C	140