




Brushless Servo Motors

SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



TECHNICAL DATA

Motor Type

B63.10Q 10 Nm - 4500 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B63.10Q
Stall torque ($\theta t=105^{\circ}\text{C}$) M_o Nm	10
Rated speed n rpm	4500
Rated power P_n kW	3.6
Rated torque ($\theta t=105^{\circ}\text{C}$) M_n Nm	7.7
Peak torque M_{pk} Nm	30
Max speed n_{max} rpm	6600
Moment of inertia J 10?? Kgm ²	4.27
Peack torque acceleration a_{pk} rad/sec ²	70258
Thermal time constant T_{th} min	35
Voltage constant k_e V _s	0.63
Torque constant k_t Nm/A	1.09
Resistance phase to phase (20°C) R_w ?	0.84
Inductance phase to phase L_w mH	7.8
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	9.2
Rated current I_n Arms	7.1
Peak current I_{pk} Arms	41.3
Power connector size	7/1

Weight kg

7.2

Mechanical Data


Design	ALUMINIUM
Degree of protection	IP 65
Bearings DE	6204 2ZC3WT
Bearings NDE	6204 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Grease Quantity	
Cooling	radiation and natural convection
Vibration Level	A (normal)
Noise Lpa db(A)	

Electrical Data

Poles	8
Voltage	400V

DIMENSIONS

- B5



IM	Square flange mm	Max length with resolver L max mm	Max length with encoder mm	Centering diameter ? CD mm	Bolt circle diameter ? BC mm	Shaft diameter ? SD mm	Shaft length SL mm	Fan Kit square mm
B5	100	150	161	?95j6	115	19k6	40	na

Lafert S.p.A., Via J.F. Kennedy 43, 30027 San Donà di Piave (Venice - Italy)