




Brushless Servo Motors

SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



TECHNICAL DATA

Motor Type

B63.06Q 7.4 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B63.06Q
Stall torque ($\theta t=105^{\circ}\text{C}$) M_o Nm	7.4
Rated speed n rpm	3000
Rated power P_n kW	2.1
Rated torque ($\theta t=105^{\circ}\text{C}$) M_n Nm	6.8
Peak torque M_{pk} Nm	18
Max speed n_{max} rpm	6600
Moment of inertia J 10?? Kgm ²	2.67
Peack torque acceleration a_{pk} rad/sec ²	67416
Thermal time constant T_{th} min	30
Voltage constant k_e V _s	0.94
Torque constant k_t Nm/A	1.63
Resistance phase to phase (20°C) R_w ?	3.5
Inductance phase to phase L_w mH	24
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	4.5
Rated current I_n Arms	4.2
Peak current I_{pk} Arms	16.5
Power connector size	7/1

Weight kg

5.3

Mechanical Data


Design	ALUMINIUM
Degree of protection	IP 65
Bearings DE	6204 2ZC3WT
Bearings NDE	6204 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Grease Quantity	
Cooling	radiation and natural convection
Vibration Level	A (normal)
Noise Lpa db(A)	

Electrical Data

Poles	8
Voltage	400V

DIMENSIONS

- B5



IM	Square flange mm	Max length with resolver L max mm	Max length with encoder mm	Centering diameter ? CD mm	Bolt circle diameter ? BC mm	Shaft diameter ? SD mm	Shaft length SL mm	Fan Kit square mm
B5	100	150	161	?95j6	115	19k6	40	na

Lafert S.p.A., Via J.F. Kennedy 43, 30027 San Donà di Piave (Venice - Italy)