



Pacchetti Motore Sincrono PM e Azionamento - IES2

MOTORE PM CON AZIONAMENTO INTEGRATO - IES2

- Massima integrazione per performance sempre migliori
- Motore IE5 + VFD IE2
- L'affidabilità di un motore AC e le prestazioni di un Brushless

HP Integral
Smart Flow Plus
solutions to meet your needs

IES2 

TECHNICAL DATA

Motor Type

HPI 112 3600 317_Smart 15 kW - 3600 rpm | Drive three-phase - 200-240V

PERFORMANCE DATA

Package Type	HPI 112 3600 317_Smart
Rated Speed rpm	3600
Rated Power kW	15
Rated Power HP	20
Rated Torque Nm	39.8
Peak Torque Nm	59.7
Rated Current Arms	31.7
Peak Current Arms	47.5
Rated input current 380Vac Arms	31.5
Rated input current 480Vac Arms	25.0
Torque Constant Nm/A	1.26
HPI Weight kg	38.5
Motor Efficiency IE code	IE5

Drive Type	Smart
Drive Efficiency IE code	IE2
HPI Efficiency IE code	IES2
HPI Efficiency ? %	NA

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6208 2Z
Bearings NDE	6306 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1001 m.a.s.l.

Drive Data

Drive Type	Smart
Supply Voltage	three-phase
Drive Voltage	200-240V
Safety Function	-
Drive Torque	constant/variable
Fieldbus	CANopen; Modbus RTU
Inputs	2 Digital; 2 Analog / Digital selectable
Outputs	1 Analog/Digital; 1 Relay

