



Pacchetti Motore Sincrono PM e Azionamento - IES2

MOTORE PM CON AZIONAMENTO INTEGRATO NDE - IES2

- Massima integrazione per ventilatori assiali
- Montaggio PAD per ottimizzare il flusso d'aria
- Efficienza Super Premium Efficiency IE5

HPAxial  **IES2**

TECHNICAL DATA

Motor Type

HPAX 112 1000 64 3 kW - 1000 rpm | Drive three-phase - 380-480V

PERFORMANCE DATA

Package Type	HPAX 112 1000 64
Rated Speed rpm	1000
Rated Power kW	3
Rated Power HP	4
Rated Torque Nm	28.6
Peak Torque Nm	43
Rated Current Arms	6.4
Voltage Constant Vs	2.6
Torque Constant Nm/A	4.50
Motor Efficiency IE code	IE5
Motor Efficiency η %	89.3
Drive Efficiency IE code	IE2
HPI Efficiency IE code	IES2

HPI Efficiency η %	87.3
-------------------------	------

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6208 2Z
Bearings NDE	6306 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.

Drive Data

Supply Voltage	three-phase
Drive Voltage	380-480V
Safety Function	-
Drive Torque	variable
Fieldbus	CANopen; Modbus RTU
Inputs	2 Digital; 2 Analog
Outputs	2 Digital; 2 Analog
Degree of Protection	IP 55