



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMQE 160L BA6 - 7.5 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 160L BA
Poles	6
kW	7.5
HP	10
rpm	981
Mn Nm	73.8
η 50%	89.1
η 75%	91.2
η 100%	91.3
cos Phi	0.73
I _N 400V	16.3
I _N 460V	-
I _N 575V	-
I _A /I _N	10.4

M_A/M_N	2.1
M_S/M_N	3.1
M_K/M_N	3.5
$J \cdot 10^{-3} \text{ kgm}^2$	136.0
kg	115.0

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	58

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.