



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMQE 180L ZG6 - 15 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 180L ZG
Poles	6
kW	15
HP	20
rpm	985
Mn Nm	145.4
η 50%	91.0
η 75%	92.9
η 100%	92.9
cos Phi	0.81
I _N 400V	28.8
I _N 460V	-
I _N 575V	-
I _A /I _N	7.3

M_A/M_N	2.0
M_S/M_N	2.0
M_K/M_N	2.1
$J \cdot 10^{-3} \text{ kgm}^2$	207
kg	245

Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	6311 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	6.500 hours
Regreasing device vertical	6.500 hours
Grease Quantity	20 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.