



Servo Motori Brushless

SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



TECHNICAL DATA

Motor Type

B28.D5Q 0.5 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

| | |
|--|---------|
| Type | B28.D5Q |
| Stall torque (Deltat=105°C) Mo Nm | 0.5 |
| Rated speed n rpm | 3000 |
| Rated power P _n kW | 154 |
| Rated torque (Deltat=105°C) Mn Nm | 0.49 |
| Peak torque M _{pk} Nm | 2 |
| Max speed n _{max} rpm | 6600 |
| Moment of inertia J 10?? Kgm ² | 0.13 |
| Peack torque acceleration a _{pk} rad/sec ² | 153846 |
| Thermal time constant T _{th} min | 34 |
| Voltage constant k _e V _s | 0.84 |
| Torque constant k _t Nm/A | 1.45 |
| Resistance phase to phase (20°C) R _w ? | 154 |
| Inductance phase to phase L _w mH | 225.7 |

| | |
|---|------|
| B.E.M.F. @ rated speed E_n Vrms | 264 |
| Stall current I_o Arms | 0.34 |
| Rated current I_n Arms | 0.34 |
| Peak current I_{pk} Arms | 1.6 |
| Power connector size | 7/1 |
| Weight kg | 1.2 |

Mechanical Data

| | |
|-----------------------------|----------------------------------|
| Design | Aluminium |
| Degree of protection | IP 65 except A side flange |
| Bearings DE | 6000 2ZC3WT |
| Bearings NDE | 6900 2ZC3WT |
| Lubrication grease | low & high temperature grease |
| Regreasing device | permanent lubrication |
| Cooling | radiation and natural convection |
| Vibration Level | A (normal) |

Electrical Data

| | |
|--|------|
| Poles | 8 |
| Voltage | 400V |
| Thermal protection threshold θ_{max} °C | 140 |