



Servo Motori Brushless

SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



TECHNICAL DATA

Motor Type

B28.E2Q 1.25 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B28.E2Q
Stall torque (Deltat=105°C) Mo Nm	1.25
Rated speed n rpm	3000
Rated power P _n kW	380
Rated torque (Deltat=105°C) Mn Nm	1.21
Peak torque M _{pk} Nm	5
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	0.31
Peack torque acceleration a _{pk} rad/sec ²	161290
Thermal time constant T _{th} min	40
Voltage constant k _e V _s	0.84
Torque constant k _t Nm/A	1.45
Resistance phase to phase (20°C) R _w ?	380
Inductance phase to phase L _w mH	58.3

B.E.M.F. @ rated speed E_n Vrms	264
Stall current I_o Arms	0.86
Rated current I_n Arms	0.83
Peak current I_{pk} Arms	4.1
Power connector size	7/1
Weight kg	2

Mechanical Data

Design	Aluminium
Degree of protection	IP 65 except A side flange
Bearings DE	6000 2ZC3WT
Bearings NDE	6900 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	8
Voltage	400V
Thermal protection threshold θ_{max} °C	140