



Servo Motori Brushless

SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



TECHNICAL DATA

Motor Type B64.10J 10 Nm - 3000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B64.10J
Stall torque (Deltat=105°C) Mo Nm	10
Rated speed n rpm	3000
Rated power P _n kW	2.6
Rated torque (Deltat=105°C) Mn Nm	8.2
Peak torque M _{pk} Nm	44
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	13.1
Peack torque acceleration a _{pk} rad/sec ²	38710
Thermal time constant T _{th} min	34
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	2.06
Inductance phase to phase L _w mH	11.4

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	6.1
Rated current I_n Arms	5
Peak current I_{pk} Arms	33.5
Power connector size	7/1
Weight kg	8.9

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6205 2ZC3WT
Bearings NDE	6303 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	10
Voltage	400V
Thermal protection threshold θ_{max} °C	140