



Servo Motori Brushless

SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



TECHNICAL DATA

Motor Type

B71.12Q 17 Nm - 2000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B71.12Q
Stall torque (Deltat=105°C) Mo Nm	17
Rated speed n rpm	2000
Rated power P _n kW	3.3
Rated torque (Deltat=105°C) Mn Nm	15.8
Peak torque M _{pk} Nm	41.4
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	8.2
Peack torque acceleration a _{pk} rad/sec ²	50488
Thermal time constant T _{th} min	40
Voltage constant k _e V _s	1.41
Torque constant k _t Nm/A	2.44
Resistance phase to phase (20°C) R _w ?	2.51
Inductance phase to phase L _w mH	24.5

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	7
Rated current I_n Arms	6.5
Peak current I_{pk} Arms	21.1
Power connector size	7/1
Weight kg	11.5

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6205 2ZC3WT
Bearings NDE	6203 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	8
Voltage	400V
Thermal protection threshold θ_{max} °C	140