



Servo Motori Brushless

SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



TECHNICAL DATA

Motor Type

B10.CAQ 105 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B10.CAQ
Stall torque (Deltat=105°C) Mo Nm	105
Rated speed n rpm	3000
Rated power P _n kW	13.2
Rated torque (Deltat=105°C) Mn Nm	42
Peak torque M _{pk} Nm	460
Max speed n _{max} rpm	4000
Moment of inertia J 10?? Kgm ²	116
Peack torque acceleration a _{pk} rad/sec ²	39655
Thermal time constant T _{th} min	58
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	0.07
Inductance phase to phase L _w mH	1.2

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	64.5
Rated current I_n Arms	25.8
Peak current I_{pk} Arms	360
Power connector size	7/1.5
Weight kg	79

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6309 2ZC3WT
Bearings NDE	6207 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	8
Voltage	400V
Thermal protection threshold θ_{max} °C	140