



Servo Motori Brushless

SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



TECHNICAL DATA

Motor Type

B13.58I 58 Nm - 1500 rpm - 6 poles - 400V

PERFORMANCE DATA

Type	B13.58I
Stall torque (Deltat=105°C) Mo Nm	58
Rated speed n rpm	1500
Rated power P _n kW	7.4
Rated torque (Deltat=105°C) Mn Nm	47
Peak torque M _{pk} Nm	162
Max speed n _{max} rpm	3600
Moment of inertia J 10?? Kgm ²	90
Peack torque acceleration a _{pk} rad/sec ²	18000
Thermal time constant T _{th} min	57
Voltage constant k _e V _s	1.88
Torque constant k _t Nm/A	3.26
Resistance phase to phase (20°C) R _w ?	0.62
Inductance phase to phase L _w mH	14.8

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	17.8
Rated current I_n Arms	14.4
Peak current I_{pk} Arms	63.3
Power connector size	7/1
Weight kg	55

Mechanical Data

Design	Aluminium
Degree of protection	IP 65 except A side flange
Bearings DE	6309 2ZC3WT
Bearings NDE	6208 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	6
Voltage	400V
Thermal protection threshold θ_{max} °C	140