



Servo Motori Brushless

SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



TECHNICAL DATA

Motor Type

B16.B4Q 312 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B16.B4Q
Stall torque (Deltat=105°C) Mo Nm	312
Rated speed n rpm	3000
Rated power P _n kW	66
Rated torque (Deltat=105°C) Mn Nm	211
Peak torque M _{pk} Nm	900
Max speed n _{max} rpm	3800
Moment of inertia J 10?? Kgm ²	497
Peack torque acceleration a _{pk} rad/sec ²	18109
Thermal time constant T _{th} min	67
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	0.019
Inductance phase to phase L _w mH	0.69

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	192
Rated current I_n Arms	130
Peak current I_{pk} Arms	708
Power connector size	3/M12
Weight kg	184.5

Mechanical Data

Design	Aluminium
Degree of protection	IP 65 except A side flange
Bearings DE	6314 2ZC3WT
Bearings NDE	6309 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	8
Voltage	400V
Thermal protection threshold θ_{max} °C	140