



## Servo Motori Brushless

### SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



## TECHNICAL DATA

Motor Type

B36.03Q 3 Nm - 3000 rpm - 8 poles - 400V

## PERFORMANCE DATA

Type	B36.03Q
Stall torque (Deltat=105°C) Mo Nm	3
Rated speed n rpm	3000
Rated power P <sub>n</sub> kW	848
Rated torque (Deltat=105°C) Mn Nm	2.7
Peak torque M <sub>pk</sub> Nm	10.5
Max speed n <sub>max</sub> rpm	6600
Moment of inertia J 10?? Kgm <sup>2</sup>	1.22
Peack torque acceleration a <sub>pk</sub> rad/sec <sup>2</sup>	86066
Thermal time constant T <sub>th</sub> min	38
Voltage constant k <sub>e</sub> V <sub>s</sub>	0.84
Torque constant k <sub>t</sub> Nm/A	1.45
Resistance phase to phase (20°C) R <sub>w</sub> ?	11.1
Inductance phase to phase L <sub>w</sub> mH	28

<b>B.E.M.F. @ rated speed <math>E_n</math> Vrms</b>	264
<b>Stall current <math>I_o</math> Arms</b>	2.1
<b>Rated current <math>I_n</math> Arms</b>	1.9
<b>Peak current <math>I_{pk}</math> Arms</b>	8.9
<b>Power connector size</b>	7/1
<b>Weight kg</b>	4.4

## Mechanical Data

<b>Design</b>	Aluminium
<b>Degree of protection</b>	IP 65
<b>Bearings DE</b>	6004 2ZC3WT
<b>Bearings NDE</b>	6003 2ZC3WT
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device</b>	permanent lubrication
<b>Cooling</b>	radiation and natural convection
<b>Vibration Level</b>	A (normal)

## Electrical Data

<b>Poles</b>	8
<b>Voltage</b>	400V
<b>Thermal protection threshold <math>\theta_{max}</math> °C</b>	140