



## Synchronous PM Motor and Drive Packages - IES2

### PM MOTOR WITH INTEGRATED DRIVE - IES2

- Maximum integration for increasingly performance
- IE5 motor + IE2 VFD
- Combination of AC motor's reliability and Brushless Servomotor's performance

**HP Integral**  
Smart Flow Plus  
solutions to meet your needs

**IES2** 

## TECHNICAL DATA

### Motor Type

HPI 90 1500 85\_Smart 4 kW - 1500 rpm | Drive three-phase - 380-480V

## PERFORMANCE DATA

| Package Type                    | HPI 90 1500 85_Smart |
|---------------------------------|----------------------|
| Rated Speed rpm                 | 1500                 |
| Rated Power kW                  | 4                    |
| Rated Power HP                  | 5.5                  |
| Rated Torque Nm                 | 25.5                 |
| Peak Torque Nm                  | 38.3                 |
| Rated Current Arms              | 8.5                  |
| Peak Current Arms               | 12.7                 |
| Rated input current 380Vac Arms | 8.8                  |
| Rated input current 480Vac Arms | 7.0                  |
| Torque Constant Nm/A            | 3.0                  |
| HPI Weight kg                   | 20.5                 |
| Motor Efficiency IE code        | IE5                  |

|                                 |       |
|---------------------------------|-------|
| <b>Drive Type</b>               | Smart |
| <b>Drive Efficiency IE code</b> | IE2   |
| <b>HPI Efficiency IE code</b>   | IES2  |
| <b>HPI Efficiency ? %</b>       | 91.3  |

## Mechanical Data

|                             |                               |
|-----------------------------|-------------------------------|
| <b>Design</b>               | ALUMINIUM                     |
| <b>Degree of protection</b> | IP 55                         |
| <b>Bearings DE</b>          | 6206 2Z                       |
| <b>Bearings NDE</b>         | 6304 2Z                       |
| <b>Lubrication grease</b>   | low & high temperature grease |
| <b>Regreasing device</b>    | permanent lubrication         |
| <b>Cooling</b>              | IC 411                        |
| <b>Vibration Level</b>      | A (normal)                    |

## Electrical Data

|                              |                |
|------------------------------|----------------|
| <b>Supply Voltage</b>        | 400V - 50Hz    |
| <b>Duty type</b>             | S1             |
| <b>Insulation class</b>      | F              |
| <b>Direction of rotation</b> | bidirectional  |
| <b>Ambient temperature</b>   | -15°C / +40 °C |
| <b>Altitude</b>              | 1001 m.a.s.l.  |

## Drive Data

|                        |                                          |
|------------------------|------------------------------------------|
| <b>Drive Type</b>      | Smart                                    |
| <b>Supply Voltage</b>  | three-phase                              |
| <b>Drive Voltage</b>   | 380-480V                                 |
| <b>Safety Function</b> | -                                        |
| <b>Drive Torque</b>    | constant/variable                        |
| <b>Fieldbus</b>        | CANopen; Modbus RTU                      |
| <b>Inputs</b>          | 2 Digital; 2 Analog / Digital selectable |
| <b>Outputs</b>         | 1 Analog/Digital; 1 Relay                |

