



## Synchronous PM Motor and Drive Packages - IES2

### PM MOTOR WITH INTEGRATED DRIVE - IES2

- Maximum integration for increasingly performance
- IE5 motor + IE2 VFD
- Combination of AC motor's reliability and Brushless Servomotor's performance

**HP Integral**  
Smart Flow Plus  
solutions to meet your needs

**IES2**

## TECHNICAL DATA

### Motor Type

HPI 90 1800 63\_Plus 3 kW - 1800 rpm | Drive three-phase - 500-600V

## PERFORMANCE DATA

|  |                     |
|--|---------------------|
| <b>Package Type</b>                    | HPI 90 1800 63_Plus |
| <b>Rated Speed rpm</b>                 | 1800                |
| <b>Rated Power kW</b>                  | 3                   |
| <b>Rated Power HP</b>                  | 4                   |
| <b>Rated Torque Nm</b>                 | 15.9                |
| <b>Peak Torque Nm</b>                  | 23.9                |
| <b>Rated Current Arms</b>              | 6.3                 |
| <b>Peak Current Arms</b>               | 9.5                 |
| <b>Rated input current 380Vac Arms</b> | 6.6                 |
| <b>Rated input current 480Vac Arms</b> | 5.2                 |
| <b>Torque Constant Nm/A</b>            | 2.5                 |
| <b>HPI Weight kg</b>                   | 17.5                |
| <b>Motor Efficiency IE code</b>        | IE5                 |

|                                 |       |
|---------------------------------|-------|
| <b>Drive Type</b>               | Smart |
| <b>Drive Efficiency IE code</b> | IE2   |
| <b>HPI Efficiency IE code</b>   | IES2  |
| <b>HPI Efficiency ? %</b>       | 90.4  |

## Mechanical Data

|                             |                               |
|-----------------------------|-------------------------------|
| <b>Design</b>               | ALUMINIUM                     |
| <b>Degree of protection</b> | IP 55                         |
| <b>Bearings DE</b>          | 6206 2Z                       |
| <b>Bearings NDE</b>         | 6304 2Z                       |
| <b>Lubrication grease</b>   | low & high temperature grease |
| <b>Regreasing device</b>    | permanent lubrication         |
| <b>Cooling</b>              | IC 411                        |
| <b>Vibration Level</b>      | A (normal)                    |

## Electrical Data

|                              |                |
|------------------------------|----------------|
| <b>Supply Voltage</b>        | 400V - 50Hz    |
| <b>Duty type</b>             | S1             |
| <b>Insulation class</b>      | F              |
| <b>Direction of rotation</b> | bidirectional  |
| <b>Ambient temperature</b>   | -15°C / +40 °C |
| <b>Altitude</b>              | 1001 m.a.s.l.  |

## Drive Data

|                        |  |
|------------------------|--|
| <b>Drive Type</b>      | Plus   |
| <b>Supply Voltage</b>  | three-phase  |
| <b>Drive Voltage</b>   | 500-600V   |
| <b>Safety Function</b> | STO/PLC  |
| <b>Drive Torque</b>    | constant/variable                                      |
| <b>Fieldbus</b>        | CANopen; Modbus RTU                                    |
| <b>Inputs</b>          | 3 Digital (+3 optional); 2 Analog / Digital selectable |
| <b>Outputs</b>         | 2 Analog / Digital; 2 Relays (+3 optional)             |

