

Synchronous PM Motor and Drive Packages - IES2

PM MOTOR AND COMBINED DRIVE - IES2

- Plug & Play solution
- Total speed control
- IP20 or IP66 / NEMA 4X outdoor
- Three package configurations



HP Combi
 Smart Flow Plus
 solutions to meet your needs

IES2 

TECHNICAL DATA

Motor Type

HPC 160 1800_Plus_IP66 18.5 kW - 1800 rpm | Drive three-phase - 380-480V

PERFORMANCE DATA

Package Type	HPC 160 1800_Plus_IP66
Rated Speed rpm	1800
Rated Power kW	18.5
Rated Power HP	25
Rated Torque Nm	98.0
Peak Torque Nm	245
Voltage Constant Vs	1.45
Torque Constant Nm/A	2.5
B.E.M.F. @ rated speed Vrs	272
Rated Current Arms	39.1
Motor Efficiency IE code	IE5
Motor Efficiency η %	94.6
Motor Weight Kg	75

Drive Type	Plus
Drive Size	4
Drive Efficiency IE code	IE2
HPC Efficiency IE code	IES2
HPC Efficiency ? %	93.5

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6310 2Z
Bearings NDE	6310 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Motor Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.

Drive Data

Drive Type	Plus
Drive Size	4
Supply Voltage	three-phase
Drive Voltage	380-480V
Safety Function	STO/PLC
Drive Torque	constant/variable
Fieldbus	CANopen; Modbus RTU

Inputs	3 Digital (+3 optional); 2 Analog / Digital selectable
Outputs	2 Analog / Digital; 2 Relays (+3 optional)
Degree of Protection	IP 66