



AC Three-phase Motors - IE4/IE3/IE2/IE1

SUPER PREMIUM EFFICIENCY MOTORS - IE4/CURUS

- Wide range from 0.75 to 200kW
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs



TECHNICAL DATA

Motor Type

AMQE 315L G6 - 132 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 315L G
Poles	6
kW	132
HP	180
rpm	990
Mn Nm	1273.0
η 50%	94.1
η 75%	96.0
η 100%	96.0
cos Phi	0.86
I_N 400V	231.0
I_N 460V	-
I_N 575V	-
I_A/I_N	6.8

M_A/M_N	2.0
M_S/M_N	2.0
M_K/M_N	2.0
$J \cdot 10^{-3} \text{ kgm}^2$	6120
kg	1250

Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	NU319 - 6319 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	5.500 hours
Regreasing device vertical	5.500 hours
Grease Quantity	50 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	71

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.