



AC Three-phase Motors - IE4/IE3/IE2/IE1

TWO SPEED MOTORS

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AMV 80Z BA4/6 - 0.75/0.25 kW - 4/6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMV 80Z BA
Poles	4/6
kW	0.75/0.25
HP	1/0.33
rpm	1400/940
Mn Nm	5.1/2.5
η 100%	70/60
cos Phi	0.82/0.72
I_N 400V	1.8/0.8
I_N 380-420V	1.9/0.9
I_A/I_N	4.2/2.6
M_A/M_N	1.6/1.3
J 10 ⁻³ kgm ²	4.05
kg	14.0

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6204/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	48

Electrical Data

Voltage	400V - 50Hz
Connection	SEPARATE WINDINGS