



AC Three-phase Motors - IE4/IE3/IE2/IE1

TWO SPEED MOTORS

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AMV 90L AA6/8 - 0.55/0.22 kW - 6/8 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMV 90L AA
Poles	6/8
kW	0.55/0.22
HP	0.75/0.3
rpm	960/740
Mn Nm	5.5/2.8
η 100%	65/47
cos Phi	0.62/0.51
I_N 400V	2.0/1.4
I_N 380-420V	2.1/1.5
I_A/I_N	3.9/2.9
M_A/M_N	2.5/2.1
J 10 ⁻³ kgm ²	4.78
kg	16.2

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	46

Electrical Data

Voltage	400V - 50Hz
Connection	SEPARATE WINDINGS