



Brushless Servo Motors

SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



TECHNICAL DATA

Motor Type

B63.06Q 7.4 Nm - 4500 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B63.06Q
Stall torque (Deltat=105°C) Mo Nm	7.4
Rated speed n rpm	4500
Rated power P _n kW	2.9
Rated torque (Deltat=105°C) Mn Nm	6.2
Peak torque M _{pk} Nm	18
Max speed n _{max} rpm	6600
Moment of inertia J 10 ⁻⁴ Kgm ²	2.67
Peack torque acceleration a _{pk} rad/sec ²	67416
Thermal time constant T _{th} min	30
Voltage constant k _e V _s	0.63
Torque constant k _t Nm/A	1.09
Resistance phase to phase (20°C) R _w ?	1.5
Inductance phase to phase L _w mH	10.8

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	6.8
Rated current I_n Arms	5.7
Peak current I_{pk} Arms	24.8
Power connector size	7/1
Weight kg	5.3

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6204 2ZC3WT
Bearings NDE	6204 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	8
Voltage	400V
Thermal protection threshold θ_{max} °C	140