



Brushless Servo Motors

SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



TECHNICAL DATA

Motor Type

B64.12J 12 Nm - 3000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B64.12J
Stall torque (Deltat=105°C) Mo Nm	12
Rated speed n rpm	3000
Rated power P _n kW	3
Rated torque (Deltat=105°C) Mn Nm	9.5
Peak torque M _{pk} Nm	53
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	15.6
Peack torque acceleration a _{pk} rad/sec ²	38358
Thermal time constant T _{th} min	37
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	1.52
Inductance phase to phase L _w mH	8.8

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	7.4
Rated current I_n Arms	5.8
Peak current I_{pk} Arms	40.3
Power connector size	7/1
Weight kg	10

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6205 2ZC3WT
Bearings NDE	6303 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	10
Voltage	400V
Thermal protection threshold θ_{max} °C	140