



Brushless Servo Motors

SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



TECHNICAL DATA

Motor Type

B10.62Q 93 Nm - 1500 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B10.62Q
Stall torque (Deltat=105°C) Mo Nm	93
Rated speed n rpm	1500
Rated power P _n kW	13.8
Rated torque (Deltat=105°C) Mn Nm	88
Peak torque M _{pk} Nm	265
Max speed n _{max} rpm	4000
Moment of inertia J 10 ⁻⁴ Kgm ²	72
Peack torque acceleration a _{pk} rad/sec ²	36806
Thermal time constant T _{th} min	56
Voltage constant k _e V _s	1.88
Torque constant k _t Nm/A	3.26
Resistance phase to phase (20°C) R _w ?	0.54
Inductance phase to phase L _w mH	8.6

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	28.6
Rated current I_n Arms	27
Peak current I_{pk} Arms	107
Power connector size	7/1
Weight kg	53

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6309 2ZC3WT
Bearings NDE	6207 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	8
Voltage	400V
Thermal protection threshold θ_{max} °C	140