



Brushless Servo Motors

SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



TECHNICAL DATA

Motor Type

B10.56J 74.5 Nm - 2000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B10.56J
Stall torque (Deltat=105°C) Mo Nm	74.5
Rated speed n rpm	2000
Rated power P _n kW	12.9
Rated torque (Deltat=105°C) Mn Nm	61.7
Peak torque M _{pk} Nm	230
Max speed n _{max} rpm	4000
Moment of inertia J 10 ⁻³ Kgm ²	102
Peack torque acceleration a _{pk} rad/sec ²	22549
Thermal time constant T _{th} min	56
Voltage constant k _e V _s	1.41
Torque constant k _t Nm/A	2.44
Resistance phase to phase (20°C) R _w ?	0.31
Inductance phase to phase L _w mH	5.6

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	30.4
Rated current I_n Arms	25.2
Peak current I_{pk} Arms	137
Power connector size	7/1
Weight kg	43

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6208 2ZC3WT
Bearings NDE	6206 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	10
Voltage	400V
Thermal protection threshold θ_{max} °C	140