



**Brushless Servo Motors**

**ATEX SERVO MOTORS - ZONE 2-22**

- Zone 2- 22 – category 3G (gas) and 3D (dust)



**TECHNICAL DATA**

**Motor Type**

B28.E2Q 1.25 Nm - 3000 rpm - 8 poles - 400V

**PERFORMANCE DATA**

<b>Type</b>	B28.E2Q
<b>Stall torque (Deltat=105°C) Mo Nm</b>	1.25
<b>Rated speed n rpm</b>	3000
<b>Rated power P<sub>n</sub> kW</b>	380.1
<b>Rated torque (Deltat=105°C) Mn Nm</b>	1.21
<b>Peak torque M<sub>pk</sub> Nm</b>	5
<b>Max speed n<sub>max</sub> rpm</b>	6600
<b>Moment of inertia J 10?? Kgm<sup>2</sup></b>	0.31
<b>Peack torque acceleration a<sub>pk</sub> rad/sec<sup>2</sup></b>	161290
<b>Thermal time constant T<sub>th</sub> min</b>	40
<b>Thermal protection threshold ?max °C</b>	140
<b>Voltage constant k<sub>e</sub> V<sub>s</sub></b>	0.84
<b>Torque constant k<sub>t</sub> Nm/A</b>	1.45
<b>Resistance phase to phase (20°C) R<sub>w</sub> ?</b>	38.6

Inductance phase to phase $L_w$ mH	58.3
B.E.M.F. @ rated speed $E_n$ Vrms	264
Stall current $I_o$ Arms	0.86
Rated current $I_n$ Arms	0.83
Peak current $I_{pk}$ Arms	4.1
Power connector size	7/1

## Electrical Data

Weight kg	2
Poles	8
Voltage	400V