



Brushless Servo Motors

ATEX SERVO MOTORS - ZONE 2-22

- Zone 2- 22 – category 3G (gas) and 3D (dust)



TECHNICAL DATA

Motor Type

B30.D7J 0.7 Nm - 6000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B30.D7J
Stall torque (Deltat=105°C) Mo Nm	0.7
Rated speed n rpm	6000
Rated power P _n kW	380
Rated torque (Deltat=105°C) Mn Nm	0.6
Peak torque M _{pk} Nm	2
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	0.22
Peack torque acceleration a _{pk} rad/sec ²	100000
Thermal time constant T _{th} min	18
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	0.47
Torque constant k _t Nm/A	0.81
Resistance phase to phase (20°C) R _w ?	26.7

Inductance phase to phase L_w mH	26.9
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	0.86
Rated current I_n Arms	0.74
Peak current I_{pk} Arms	3.2
Power connector size	8/-

Electrical Data

Weight kg	0.8
Poles	10
Voltage	400V