



### Brushless Servo Motors

### ATEX SERVO MOTORS - ZONE 2-22

- Zone 2- 22 – category 3G (gas) and 3D (dust)



## TECHNICAL DATA

Motor Type

B63.10Q 10 Nm - 3000 rpm - 8 poles - 400V

## PERFORMANCE DATA

Type	B63.10Q
Stall torque (Deltat=105°C) Mo Nm	10
Rated speed n rpm	3000
Rated power P <sub>n</sub> kW	2.7
Rated torque (Deltat=105°C) Mn Nm	8.75
Peak torque M <sub>pk</sub> Nm	30
Max speed n <sub>max</sub> rpm	6600
Moment of inertia J 10?? Kgm <sup>2</sup>	4.27
Peack torque acceleration a <sub>pk</sub> rad/sec <sup>2</sup>	70258
Thermal time constant T <sub>th</sub> min	35
Thermal protection threshold ?max °C	140
Voltage constant k <sub>e</sub> V <sub>s</sub>	0.94
Torque constant k <sub>t</sub> Nm/A	1.63
Resistance phase to phase (20°C) R <sub>w</sub> ?	1.9

Inductance phase to phase $L_w$ mH	17.4
B.E.M.F. @ rated speed $E_n$ Vrms	296
Stall current $I_o$ Arms	6.1
Rated current $I_n$ Arms	5.4
Peak current $I_{pk}$ Arms	27.5
Power connector size	7/1

## Electrical Data

Weight kg	7.2
Poles	8
Voltage	400V