



Brushless Servo Motors

ATEX SERVO MOTORS - ZONE 2-22

- Zone 2- 22 – category 3G (gas) and 3D (dust)



TECHNICAL DATA

Motor Type

B63.06Q 6 Nm - 4500 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B63.06Q
Stall torque (Deltat=105°C) Mo Nm	6
Rated speed n rpm	4500
Rated power P _n kW	2.2
Rated torque (Deltat=105°C) Mn Nm	4.65
Peak torque M _{pk} Nm	18
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	2.67
Peack torque acceleration a _{pk} rad/sec ²	67416
Thermal time constant T _{th} min	30
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	0.63
Torque constant k _t Nm/A	1.09
Resistance phase to phase (20°C) R _w ?	1.5

Inductance phase to phase L_w mH	10.8
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	5.5
Rated current I_n Arms	4.3
Peak current I_{pk} Arms	24.8
Power connector size	7/1

Electrical Data

Weight kg	5.3
Poles	8
Voltage	400V