



Brushless Servo Motors

ATEX SERVO MOTORS - ZONE 2-22

- Zone 2- 22 – category 3G (gas) and 3D (dust)



TECHNICAL DATA

Motor Type

B16.C4Q 140 Nm - 2000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B16.C4Q
Stall torque (Deltat=105°C) Mo Nm	140
Rated speed n rpm	2000
Rated power P _n kW	18
Rated torque (Deltat=105°C) Mn Nm	86
Peak torque M _{pk} Nm	475
Max speed n _{max} rpm	3800
Moment of inertia J 10?? Kgm ²	290
Peack torque acceleration a _{pk} rad/sec ²	16379
Thermal time constant T _{th} min	63
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	1.41
Torque constant k _t Nm/A	2.44
Resistance phase to phase (20°C) R _w ?	0.080

Inductance phase to phase L_w mH	2.38
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	57
Rated current I_n Arms	35
Peak current I_{pk} Arms	
Power connector size	7/1.5

Electrical Data

Weight kg	119
Poles	8
Voltage	400V