



Brushless Servo Motors

ATEX SERVO MOTORS - ZONE 2-22

- Zone 2- 22 – category 3G (gas) and 3D (dust)



TECHNICAL DATA

Motor Type

B16.B4Q 240 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B16.B4Q
Stall torque (Deltat=105°C) Mo Nm	240
Rated speed n rpm	3000
Rated power P _n kW	28
Rated torque (Deltat=105°C) Mn Nm	88
Peak torque M _{pk} Nm	900
Max speed n _{max} rpm	3800
Moment of inertia J 10?? Kgm ²	497
Peack torque acceleration a _{pk} rad/sec ²	18109
Thermal time constant T _{th} min	67
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	0.019

Inductance phase to phase L_w mH	0.69
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	147
Rated current I_n Arms	54
Peak current I_{pk} Arms	
Power connector size	3/M10

Electrical Data

Weight kg	173
Poles	8
Voltage	400V