



Brushless Servo Motors

ATEX SERVO MOTORS - ZONE 2-22

- Zone 2- 22 – category 3G (gas) and 3D (dust)



TECHNICAL DATA

Motor Type

B36.03Q 3 Nm - 6000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B36.03Q
Stall torque (Deltat=105°C) Mo Nm	3
Rated speed n rpm	6000
Rated power P _n kW	1508
Rated torque (Deltat=105°C) Mn Nm	2.4
Peak torque M _{pk} Nm	10.5
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	1.22
Peack torque acceleration a _{pk} rad/sec ²	86066
Thermal time constant T _{th} min	38
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	0.42
Torque constant k _t Nm/A	0.73
Resistance phase to phase (20°C) R _w ?	2.77

Inductance phase to phase L_w mH	7
B.E.M.F. @ rated speed E_n Vrms	264
Stall current I_o Arms	4.1
Rated current I_n Arms	3.3
Peak current I_{pk} Arms	17.8
Power connector size	7/1

Electrical Data

Weight kg	4.4
Poles	8
Voltage	400V