



Brushless Servo Motors

ATEX SERVO MOTORS - ZONE 2-22

- Zone 2- 22 – category 3G (gas) and 3D (dust)



TECHNICAL DATA

Motor Type

B71.20Q 20 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

| | |
|--|---------|
| Type | B71.20Q |
| Stall torque (Deltat=105°C) Mo Nm | 20 |
| Rated speed n rpm | 3000 |
| Rated power P _n kW | 5.5 |
| Rated torque (Deltat=105°C) Mn Nm | 17.5 |
| Peak torque M _{pk} Nm | 69 |
| Max speed n _{max} rpm | 6600 |
| Moment of inertia J 10?? Kgm ² | 13.1 |
| Peack torque acceleration a _{pk} rad/sec ² | 52672 |
| Thermal time constant T _{th} min | 46 |
| Thermal protection threshold ?max °C | 140 |
| Voltage constant k _e V _s | 0.94 |
| Torque constant k _t Nm/A | 1.63 |
| Resistance phase to phase (20°C) R _w ? | 0.65 |

| | |
|------------------------------------|------|
| Inductance phase to phase L_w mH | 6.3 |
| B.E.M.F. @ rated speed E_n Vrms | 296 |
| Stall current I_o Arms | 12.3 |
| Rated current I_n Arms | 10.7 |
| Peak current I_{pk} Arms | |
| Power connector size | 7/1 |

Electrical Data

| | |
|-----------|------|
| Weight kg | 17.5 |
| Poles | 8 |
| Voltage | 400V |