



Brushless Servo Motors

ATEX SERVO MOTORS - ZONE 2-22

- Zone 2- 22 – category 3G (gas) and 3D (dust)



TECHNICAL DATA

Motor Type

B71.35Q 35 Nm - 2000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B71.35Q
Stall torque (Deltat=105°C) Mo Nm	35
Rated speed n rpm	2000
Rated power P _n kW	5.6
Rated torque (Deltat=105°C) Mn Nm	26.7
Peak torque M _{pk} Nm	138
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	25.5
Peack torque acceleration a _{pk} rad/sec ²	54118
Thermal time constant T _{th} min	53
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	1.41
Torque constant k _t Nm/A	2.44
Resistance phase to phase (20°C) R _w ?	0.62

Inductance phase to phase L_w mH	7.8
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	14.3
Rated current I_n Arms	10.9
Peak current I_{pk} Arms	
Power connector size	7/1

Electrical Data

Weight kg	29.6
Poles	8
Voltage	400V