



Brushless Servo Motors

ULTRA COMPACT SERVO MOTORS

- Up to 30% increased power density
- Up to 20% reduced dimensions
- Sophisticated design, intended for extreme torque stability and precision



TECHNICAL DATA

Motor Type

B28.E2U 1.2 Nm - 6000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B28.E2U
Stall torque (Deltat=105°C) Mo Nm	1.2
Rated speed n rpm	6000
Rated power P _n kW	628
Rated torque (Deltat=105°C) Mn Nm	1.00
Peak torque M _{pk} Nm	4.8
Max speed n _{max} rpm	9000
Moment of inertia J 10?? Kgm ²	0.19
Thermal time constant T _{th} min	15
Voltage constant k _e V _s	0.42
Torque constant k _t Nm/A	0.73
Resistance phase to phase (20°C) R _w ?	11.1
Inductance phase to phase L _w mH	18.8
B.E.M.F. @ rated speed E _n Vrms	264

Stall current I_o Arms	1.65
Rated current I_n Arms	1.37
Peak current I_{pk} Arms	8.3
Connection type/size	8/-
Weight kg	1.66

Mechanical Data

Design	Aluminium
Degree of protection	IP 65 except A side flange
Bearings DE	6000
Bearings NDE	6000
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Voltage	400V
Poles	10
Thermal protection threshold θ_{max} °C	na