

**Pacchetti Motore Sincrono PM e Azionamento - IES2**



**MOTORE PM E AZIONAMENTO COMBINATO - IES2**

- Soluzione Plug & Play
- Totale controllo della velocità
- Protezione IP20 o IP66 / NEMA 4X outdoor
- Tre configurazioni del pacchetto

**HP Combi**  
Smart Flow Plus  
solutions to meet your needs

**IES2** 

## TECHNICAL DATA

**Motor Type**

HPC 132 3600\_Flow\_IP20 30 kW - 3600 rpm | Drive three-phase - 500-600V

## PERFORMANCE DATA

|   |                        |
|---|------------------------|
| <b>Package Type</b>                         | HPC 132 3600_Flow_IP20 |
| <b>Rated Speed rpm</b>                      | 3600                   |
| <b>Rated Power kW</b>                       | 30                     |
| <b>Rated Power HP</b>                       | 40                     |
| <b>Rated Torque Nm</b>                      | 79.6                   |
| <b>Peak Torque Nm</b>                       | 199                    |
| <b>Voltage Constant Vs</b>                  | 0.73                   |
| <b>Torque Constant Nm/A</b>                 | 1.26                   |
| <b>B.E.M.F. @ rated speed Vrs</b>           | 272                    |
| <b>Rated Current Arms</b>                   | 62.9                   |
| <b>Motor Efficiency IE code</b>             | IE5                    |
| <b>Motor Efficiency <math>\eta</math> %</b> | 94.9                   |
| <b>Motor Weight Kg</b>                      | 85                     |

|                                 |      |
|---------------------------------|------|
| <b>Drive Type</b>               | Flow |
| <b>Drive Size</b>               | 5    |
| <b>Drive Efficiency IE code</b> | IE2  |
| <b>HPC Efficiency IE code</b>   | IES2 |
| <b>HPC Efficiency ? %</b>       | 93.1 |

## Electrical Data

|                              |                |
|------------------------------|----------------|
| <b>Motor Supply Voltage</b>  | 400V - 50Hz    |
| <b>Duty type</b>             | S1             |
| <b>Insulation class</b>      | F              |
| <b>Direction of rotation</b> | bidirectional  |
| <b>Ambient temperature</b>   | -15°C / +40 °C |
| <b>Altitude</b>              | 1000 m.a.s.l.  |

## Drive Data

|                             |  |
|-----------------------------|--|
| <b>Drive Type</b>           | Flow   |
| <b>Drive Size</b>           | 5  |
| <b>Supply Voltage</b>       | three-phase  |
| <b>Drive Voltage</b>        | 500-600V   |
| <b>Safety Function</b>      | STO/PLC  |
| <b>Drive Torque</b>         | variable   |
| <b>Fieldbus</b>             | BACnet MS/TP; Modbus RTU                               |
| <b>Inputs</b>               | 3 Digital (+3 optional); 2 Analog / Digital selectable |
| <b>Outputs</b>              | 2 Analog / Digital; 2 Relays (+3 optional)             |
| <b>Degree of Protection</b> | IP 20  |