



## Pacchetti Motore Sincrono PM e Azionamento - IES2

### MOTORE PM E AZIONAMENTO COMBINATO - IES2

- Soluzione Plug & Play
- Totale controllo della velocità
- Protezione IP20 o IP66 / NEMA 4X outdoor
- Tre configurazioni del pacchetto

**HP Combi**  
Smart Flow Plus  
solutions to meet your needs

**IES2** 

## TECHNICAL DATA

### Motor Type

HPC 160 1500\_Plus\_IP20 30 kW - 1500 rpm | Drive three-phase - 200-240V

## PERFORMANCE DATA

|                            |                        |
|----------------------------|------------------------|
| Package Type               | HPC 160 1500_Plus_IP20 |
| Rated Speed rpm            | 1500                   |
| Rated Power kW             | 30                     |
| Rated Power HP             | 40                     |
| Rated Torque Nm            | 191                    |
| Peak Torque Nm             | 477                    |
| Voltage Constant Vs        | 1.73                   |
| Torque Constant Nm/A       | 2.5                    |
| B.E.M.F. @ rated speed Vrs | 272                    |
| Rated Current Arms         | 63.7                   |
| Motor Efficiency IE code   | IE5                    |
| Motor Efficiency $\eta$ %  | 95.3                   |
| Motor Weight Kg            | 115                    |

|                                 |      |
|---------------------------------|------|
| <b>Drive Type</b>               | Flow |
| <b>Drive Size</b>               | 5    |
| <b>Drive Efficiency IE code</b> | IE2  |
| <b>HPC Efficiency IE code</b>   | IES2 |
| <b>HPC Efficiency ? %</b>       | 93.7 |

## Electrical Data

|                              |                |
|------------------------------|----------------|
| <b>Motor Supply Voltage</b>  | 400V - 50Hz    |
| <b>Duty type</b>             | S1             |
| <b>Insulation class</b>      | F              |
| <b>Direction of rotation</b> | bidirectional  |
| <b>Ambient temperature</b>   | -15°C / +40 °C |
| <b>Altitude</b>              | 1000 m.a.s.l.  |

## Drive Data

|                             |                                                        |
|-----------------------------|--------------------------------------------------------|
| <b>Drive Type</b>           | Plus                                                   |
| <b>Drive Size</b>           | 5                                                      |
| <b>Supply Voltage</b>       | three-phase                                            |
| <b>Drive Voltage</b>        | 200-240V                                               |
| <b>Safety Function</b>      | STO/PLC                                                |
| <b>Drive Torque</b>         | constant/variable                                      |
| <b>Fieldbus</b>             | CANopen; Modbus RTU                                    |
| <b>Inputs</b>               | 3 Digital (+3 optional); 2 Analog / Digital selectable |
| <b>Outputs</b>              | 2 Analog / Digital; 2 Relays (+3 optional)             |
| <b>Degree of Protection</b> | IP 20                                                  |