



## Motori Asincroni Trifase - IE4/IE3/IE2/IE1

### MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



## TECHNICAL DATA

Motor Type

AMQE 315S G6 - 75 kW - 6 poles - 400V - 50Hz

## PERFORMANCE DATA

| Type                           | AMQE 315S G |
|--------------------------------|-------------|
| Poles                          | 6           |
| kW                             | 75          |
| HP                             | 100         |
| rpm                            | 990         |
| Mn Nm                          | 723.5       |
| $\eta$ 50%                     | 93.5        |
| $\eta$ 75%                     | 95.4        |
| $\eta$ 100%                    | 95.4        |
| cos Phi                        | 0.84        |
| I <sub>N</sub> 400V            | 135.0       |
| I <sub>N</sub> 460V            | -           |
| I <sub>N</sub> 575V            | -           |
| I <sub>A</sub> /I <sub>N</sub> | 6.6         |

|                                 |      |
|---------------------------------|------|
| $M_A/M_N$                       | 2.0  |
| $M_S/M_N$                       | 2.0  |
| $M_K/M_N$                       | 2.0  |
| $J \cdot 10^{-3} \text{ kgm}^2$ | 4110 |
| kg                              | 960  |

## Mechanical Data

|                              |                               |
|------------------------------|-------------------------------|
| Design                       | Cast iron                     |
| Degree of protection         | IP 55                         |
| Bearings DE/NDE              | NU319 - 6319 C3               |
| Lubrication grease           | low & high temperature grease |
| Regreasing device horizontal | 5.500 hours                   |
| Regreasing device vertical   | 5.500 hours                   |
| Grease Quantity              | 50 gr                         |
| Cooling                      | IC 411                        |
| Vibration Level              | A (normal)                    |
| Noise Lpa db(A)              | 71                            |

## Electrical Data

|                       |                |
|-----------------------|----------------|
| Voltage               | 400V - 50Hz    |
| Connection            | ?/Y 400/690V   |
| Duty type             | S1             |
| Thermal protection    | na             |
| Insulation class      | F              |
| Direction of rotation | bidirectional  |
| Ambient temperature   | -20°C / +40 °C |
| Altitude              | 1000 m.a.s.l.  |