



## Servo Motori Brushless

### SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



## TECHNICAL DATA

Motor Type

B16.300Q 300 Nm - 2500 rpm - 8 poles - 400V

## PERFORMANCE DATA

| Type                                                           | B16.300Q |
|----------------------------------------------------------------|----------|
| Stall torque (Deltat=105°C) Mo Nm                              | 300      |
| Rated speed n rpm                                              | 2500     |
| Rated power P <sub>n</sub> kW                                  | 39       |
| Rated torque (Deltat=105°C) Mn Nm                              | 150      |
| Peak torque M <sub>pk</sub> Nm                                 | 1150     |
| Max speed n <sub>max</sub> rpm                                 | 3800     |
| Moment of inertia J 10 <sup>-4</sup> Kgm <sup>2</sup>          | 622      |
| Peack torque acceleration a <sub>pk</sub> rad/sec <sup>2</sup> | 18489    |
| Thermal time constant T <sub>th</sub> min                      | 69       |
| Voltage constant k <sub>e</sub> V <sub>s</sub>                 | 1.13     |
| Torque constant k <sub>t</sub> Nm/A                            | 1.96     |
| Resistance phase to phase (20°C) R <sub>w</sub> ?              | 0.016    |
| Inductance phase to phase L <sub>w</sub> mH                    | 0.65     |

|                                                     |       |
|-----------------------------------------------------|-------|
| <b>B.E.M.F. @ rated speed <math>E_n</math> Vrms</b> | 296   |
| <b>Stall current <math>I_o</math> Arms</b>          | 153   |
| <b>Rated current <math>I_n</math> Arms</b>          | 77    |
| <b>Peak current <math>I_{pk}</math> Arms</b>        | 752   |
| <b>Power connector size</b>                         | 3/M10 |
| <b>Weight kg</b>                                    | 205   |

## Mechanical Data

|                             |                                  |
|-----------------------------|----------------------------------|
| <b>Design</b>               | Aluminium                        |
| <b>Degree of protection</b> | IP 65 except A side flange       |
| <b>Bearings DE</b>          | 6314 2ZC3WT                      |
| <b>Bearings NDE</b>         | 6309 2ZC3WT                      |
| <b>Lubrication grease</b>   | low & high temperature grease    |
| <b>Regreasing device</b>    | permanent lubrication            |
| <b>Cooling</b>              | radiation and natural convection |
| <b>Vibration Level</b>      | A (normal)                       |

## Electrical Data

|                                                                  |      |
|------------------------------------------------------------------|------|
| <b>Poles</b>                                                     | 8    |
| <b>Voltage</b>                                                   | 400V |
| <b>Thermal protection threshold <math>\theta_{max}</math> °C</b> | 140  |